

产品 **Kusapour IBP (PPD for Group I and II oils)**

特性 **Kusapour IBP** 是一款溶解在矿物油中的聚甲基丙烯酸酯类的粘性溶液，推荐用于润滑基础油中作为降凝剂使用，能完全溶于石油溶剂类（I 和 II 类）。

技术数据		典型	规格		
		数值	最小	最大	
外观	:	清晰，粘稠液体			
颜色	:	淡黄至琥珀			
粘度 @ 100°C (cSt)	:		50	400	ASTM D445
密度 25°C (g/cm ³)	:		0.88	0.94	ASTM D4052
闪点°C (COC)	:		150		ASTM D92

应用 **Kusapour IBP** 一般在单级和多级曲轴箱油的工业油和齿轮油中用作降凝剂。除了降低倾点的功能外，**Kusapour IBP** 在一定的剪切条件下可以有效控制低温粘度，根据基础油和所需的倾点，添加量介于 0.1 – 0.5 % 之间。

存储 该产品在密封的原始容器中可在 + 5°C 至 + 45°C 的温度范围内安全地保存至少 12 个月。

The data contained herein serve as general information for our customers only and are not binding. The data contained herein have been collected to the best of our knowledge and do not constitute any advice or warranty to our customers for any specific application. It is up to our customer at their own risk to determine the suitability of each product for their individual purposes. The products are sold without any representation, warranty or guarantee either expressed or implied. Our liability is limited to the value of the supplied merchandise.