

AOS 6340

抗乳化，不染色和脱水性的防锈缓蚀剂

描述

AOS 6340 是一款油溶性和溶剂型防锈助剂包，专为工业和家庭应用而设计，提供一层薄而软的薄膜，同时还用作渗透剂和润滑剂。具有脱水性和不染色的特性。它还提供盐雾保护，这是一种非常罕见的不染色产品。

特性

		测试方法	规格
密度@ 15.6 °C	(g/ml)	ASTM D-1298	0.91 – 0.95
酸值	(mg KOH/g)	ASTM D-974	9 - 17
皂化值	(mg KOH/g)	ASTM D-94	38 - 60

推荐

AOS 6340	3 - 10 %
矿物溶剂	Balance
or	
AOS 6340	12 %
Oil (ISO VG46)	12 %
矿物溶剂	76 %

..2..

The data contained herein serve as general information for our customers only and are not binding. The data contained herein have been collected to the best of our knowledge and do not constitute any advice or warranty to our customers for any specific application. It is up to our customer at their own risk to determine the suitability of each product for their individual purposes. The products are sold without any representation, warranty or guarantee either expressed or implied. Our liability is limited to the value of the supplied merchandise.

表现数据

% AOS 6340	% Mineral Spirits	Humidity Cabinet days pass (2)
4	96	60+

% AOS 6340	% Oil (1)	% Mineral Spirits	Humidity Cabinet days pass (2)	5% Salt Spray hours pass (2)
10	-	90	60+	15
10		80	60+	20
12	12	76	60+	45
15	15	70	60+	60

(1) ISO VG 46

(2) 喷砂板

存储

AOS 6340 可以在原装密封条件下 40°C 以下存储至少 24 个月。

The data contained herein serve as general information for our customers only and are not binding. The data contained herein have been collected to the best of our knowledge and do not constitute any advice or warranty to our customers for any specific application. It is up to our customer at their own risk to determine the suitability of each product for their individual purposes. The products are sold without any representation, warranty or guarantee either expressed or implied. Our liability is limited to the value of the supplied merchandise.