



coatmaster

measure up. contactless.

coatmaster 3D Modular

Your solution for
non-contact
coating thickness
measurement



Avoid rework and rejects.

Detect and correct deviations early in the process.



Save material.

Reduce your material consumption by up to 30%. This saves money and protects the environment.



Ensure quality.

Produce coatings with high accuracy and set new quality standards.

Technical Data

Substrate: Metal

Powder coatings before curing	5 – 300 µm
Wet coatings before drying	5 – 300 µm
Cured powder coatings	5 – 500 µm
Dried wet coatings	5 – 500 µm
Measuring time	from 20 ms
Distance tolerance	2 – 15 cm
Tilt tolerance	± 70°
Measurement on moving and jiggling parts	yes
Relative standard deviation*	<2 %
Smallest measuring point	2 mm
Works on all colors (incl. white)	yes
Real-time data access via ERP and Internet Browser	yes
Dimension HxWxD	374 x 91 x 203 mm
Weight (without battery)	1.3 kg
Measurements/battery with application non-white	up to 1,300
Standby time/battery	up to 7.5 h

All information applies to a typical coating system and substrate.

The exact limits always depend on the physical properties of the coating material.

Even if the parameters are within the specified ranges, certain combinations may not be achievable.

For an accurate assessment, please contact coatmaster AG.

Actual performance may vary, and specifications are subject to change without prior notice.

*60 µm powder coating before curing on aluminium, 5 cm working distance.



coatmaster AG

Flugplatzstrasse 5

CH-8404 Winterthur

Tel +41 52 212 02 77

info@coatmaster.com

www.coatmaster.com



Learn more

All information about
thickness measurement
with coatmaster